



Our 8 Series service body is intended for 26,000 GVWR chassis is 11', and supports up to a 12,000 lbs. capacity crane. They're built for strength and durability and will perform in rough conditions for years to come. The body has abundant storage for tools and accessories to ensure field service techs arrive at the job site prepared to complete any task.



BODY SPECIFICATIONS

GVWR: 26,000 lbs.

Body Weight: 5250 lbs.

Body Width: 94"

Body Length: 11'

Body Rating: 38,000 ft. lbs.

Body Material 10 ga. galvanized steel body shell

Storage Capacity 150 cu ft.

Cargo Deck Width: 50"

Cargo Deck Depth: 132"

Cargo Deck Floor: 3/16" tread plate construction

Side Pack Height: 40", 50", 62"

Sidepack Depth: 22"

Tailgate: 12"

Workbench Depth: 24"

STANDARD BODY FEATURES


- 10 ga. galvanized steel body construction
- 1/8" aluminum bolt-on doors with an internal frame
- Full-length piano style aluminum hinges
- Automotive-style bulb weather stripping
- Ergonomic three-point compression door latches keep compartments sealed tight.
- Aluminum drip rail above compartment doors
- 3/16" diamond tread plate floor in the cargo area to reduce the risk of slips and falls.
- Swivel D-ring tie-downs flush-mounted on the cargo area walls: Qty 6
 - 6,000 lbs. Capacity
- A fully integrated crane support structure
- 24" D tool bumper with storage compartment
 - Integrated bumper steps made with grip strut provide slip-resistant access to the cargo area.
 - 2.5" 18,000 lbs automotive-style receiver hitch
- Infinitely adjustable compartment shelves with dividers
- Bright polished knurled grab handles mounted on the rear side packs aid in safe three-point contact access to the cargo area.
- 12" aluminum slam style lockable tailgate
- Torch bottle storage compartment
 - Vented and reinforced floor
 - Torch bottle retainer with ratchet straps
- Reinforced welder riser mounting blocks on top of DS sidepack
- Safety placard and decals





ADVANCED SAFETY ELECTRONICS

- Fully integrates crane and body operations to improve safety and efficiency.
- Conveniently operate and monitor the crane, outriggers, lights and more from the main control panel and wireless remote control.
- Built-in safety features protect against jobsite hazards and ensure safe crane operation.



SCAN TO LEARN
MORE ABOUT ASE

COMPATIBLE CRANES

Summit Electric Cranes

- 4416E
- 6422E

Summit Hydraulic Cranes

- 6620
- 6629
- 7529
- 10620
- 10629

ELECTRICAL & LIGHTING

- LED Light Package
 - Grommeted and flush-mounted
 - Front and rear marker lights
 - Oval stop/tail/turn lights on the rear bumper and headache rack
 - Reverse lights on the rear bumper with a backup alarm
- LED rectangle work lights
- LED compartment strip lights
- Control lights from ASE main control panel, chassis cab panel, and crane remote
- 7-way RV style trailer plug
- Electrical wiring harnesses feature Deutsch connectors and braided protective sleeves.

PAINT

- The three-step Delfleet paint process gives the body a high-quality image and durability.
 - Phosphate wash, PPG epoxy primer, and PPG topcoat.
 - Five year PPG warranty against rust and corrosion
 - Endless color options
- Line-X protective coating applied to the cargo area, rear bumper, side pack front, top, rear, and the entire length of the bottom edge of the body provides long-lasting protection from harsh elements.
- Rubberized undercoating applied to the entire underside of the body optimizes durability.

TOOLBOXES

- Summit designed and manufactured drawer packages
- .125" aluminum construction
- Heavy-duty 600 lbs capacity roller bearing slides
- Lock-in-lock out drawer slides
- Lockable single action handle assembly
- Drawers available in 3", 5" and 7" depths
- Custom widths from 12"-50".
- .3625 riser
- Adjustable integrated top shelf or reduced top plate
- Optional egg crating
- Optional slide-out work tray
- Limited Lifetime Warranty

HYDRAULIC SYSTEM

- Open center fixed displacement gear pump
- PTO directly mounted to the transmission
- 32 gal body-mounted hydraulic reservoir

AIR COMPRESSOR SYSTEMS

- Hydraulic-driven reciprocating or rotary screw air compressor
- 40 CFM free air output at 100 psi
- 175 psi max output (reciprocating)
- 150 psi max output (rotary screw)
- Hannay ½" x 50' HD spring rewind hose reel
 - 50' air hose terminated with ½" male NPT hose end
 - Payout door on the rear of side pack
- ASME underbody air receiver
 - 19 gal air storage tank
 - Mechanical air tank moisture drain
- Norgren ½" Filter/Lubricator/Regulator

CUSTOM OPTIONS

Gang Locks

Drawer Packages

Bolt Bins

Welders

Air Compressors

All-in-one power units

Enhanced Lighting

Bumper style

Lube packages

Ladder racks

Wheel chocks

Vinyl graphics

Man-bucket

And more

