



Summit 8 Series Custom Service Truck

Liebherr

STE10904

BODY CONSTRUCTION

- 10 ga galvanized body, 14' LG
- 22" D side packs
- 54" W cargo floor
- 62" T DS compartments
- 62" T P1 & P2 compartments
- 50" T P3 & P4 compartments
- Tie-down rings on cargo area walls: Qty 6
- Aluminum bonded doors w/full length piano-style hinges
- Automotive-style weather-stripping
- Ergonomic over molded three-point compression door latches
- Aluminum drip rail over compartment doors
- Chassis batteries mounted on the front of the body

SUMMIT DRAWER SYSTEMS

- Aluminum drawer package: XXDRSA-34W-04-03-01-18D
 - Seven drawers, 34" W X 18" D x 56" T
- Aluminum drawer package: DRSA-46W-02-01-00-18D
 - Three drawers, 46" W x 18" D
- Aluminum bolt bin: PBA-21-7W x 3T
 - 21 bins, 7 bins W x 3 bins T

TORCH STORAGE COMPARTMENT

- The front section has reinforced floor, upper & lower vents
 - Torch bottle retainer w/ratchet strap
- The rear section has Unistrut & adjust. aluminum shelves: Qty 3



ELECTRICAL & LIGHTING

- LED S/T/T light package
 - Flush mounted in bumper & light bar
- LED compartment lights
- LED Work Lights: Qty 10
- Seven-way RV-style trailer plug
- Backup alarm
- Nagy Fleet backup camera
- Whelen Justice mini lightbar
- Aims Power 3000W pure sine power inverter
- 115V GFCI
- 12V power outlet

SUMMIT MODEL 10620 TELESCOPIC CRANE

- Capacity rating: 12,000 lbs. @ 5 feet
- Planetary winch @ 60' per minute
- Auto release stow hook
- Boom support & hook anchor
- Proportional hyd system
- Full hyd rear outriggers, dual extend
- 32 gal hyd reservoir
- ASE Phase 4 control system

ADDITIONAL FEATURES

- Standard headache rack
- 24" tool bumper w/door on each side
 - 2.5" receiver tube
 - Built-in grip strut steps
 - Wide belt steps: Qty 2
- Grab handles: Qty 2
- 12" H aluminum tailgate w/slam latch
- Wilton 1765 vise
- RAM laptop stand
- Hose retainer
- Aerosol can door storage racks.



MILLER ENPAK® A60GBHW ALL-IN-ONE SOLUTION

- Kubota 24.8 hp diesel engine
- Control Panels: User interface, weld output, aux power, battery charge/crank assist
- Rotary screw air compressor
 - 60 CFM @175 psi, 100% duty cycle
 - 15 gal air storage tank
 - Hannay Reels spring rewind reel w/1/2" x 50' hose & FRL
- Generator: 7000W continuous power
 - 120v outlets: Qty 2
 - 240v outlet
- Battery charger/crank assist:12/24V
 - 150A charge
 - 300A battery boost
 - Battery booster cable set
- Hyd pump: Casappa variable-displacement pump
 - 8-16 gpm 3500 psi max, open center
- Welder
 - 325A Multiprocess weld capabilities
 - 100% duty cycle
 - DC stick: 30–325A DC
 - TIG: 20–325A
 - MIG/flux-cored: 15–40V
 - 50' of 1/0 hot & ground leads
 - quick disconnects
 - 300A ground clamps & electrode holder
- 20 hyd reservoir

USED OIL SYSTEM

- 100 gal steel tank
- Lincoln 1" diaphragm pump
- Overfill prevention switch
- Samson directional valve
- Hannay Reels spring rewind reel w/3/4" x 25' suction hose
 - 30" suction wand w/a quick coupler

◦



PAINT & FINISH

- Paint: Freightliner White L0006 exterior & interior
- Line-X Ultimate Linings
 - Cargo area
 - Bumper work surface, steps, & outriggers
 - Fronts, side, tops, the rear, & lower edge of side packs
 - Wheel well reinforcement
- Rubberized underbody coating

CHASSIS SPECIFICATIONS

- 2023 Freightliner M2 106
- GVWR: 26,000 lbs
- HP: 300
- Engine: Cummins® ISB6.7™
- Transmission: Allison® 2500 Rugged Duty Series™
 - 6-spd automatic
- Exhaust brake
- CA: 90”
- Wheels: 22.5” X 8.25” Aluminum
- Tires: 11R22.5