



Summit 7 Series Performance Equipment STE11268

BODY CONSTRUCTION

- 12 ga galvanized steel, 11' LG
- 22" D side packs
- 50" W cargo floor
- 62" T D1& D2 compartments
- 50" T D3 & D4 compartments
- 62" T P1 compartment
- 50" T P2-P4 compartments
- Tie-down rings on cargo area walls: Qty 6
- Aluminum bonded doors w/full length piano-style hinges
- Automotive-style weatherstripping
- Ergonomic overmolded three-point compression door latches
- Aluminum drip rail over compartment doors

SUMMIT DRAWER SYSTEMS

- Aluminum combo drawer pack: NEW DESIGN
 - TDRSA-52T-30L-03-02-01-22R-00-01-03
 - 52" W x 18" D overall
 - One 5" full-width top drawer
 - Left side
 - Three 3" drawers
 - Two 5" drawers
 - One 7" drawer
 - Right Side
 - One 5" drawer
 - Three 7" drawers
 - The top shelf spans the full width of the compartment.



TORCH STORAGE COMPARTMENT

- The front section has reinforced floor, upper & lower vents
 - Torch bottle retainer w/ratchet strap
- The rear section has unistrut & adjust. aluminum shelves: Qty 2

ELECTRICAL & LIGHTING

- LED S/T/T light package
 - Flush mounted in bumper & light bar
- LED compartment lights
- LED Work Lights
 - Rigid 115-Degree Scene Lights: Qty 6
 - Standard Rect.: Qty 2
- Seven-way RV-style trailer plug
- Backup alarm
- Pinnacle lightbar
- Backup camera

ADDITIONAL FEATURES

- Standard Headache rack
- 24" tool bumper w/a door on each side
 - 2.5" receiver tube
 - Built-in grip strut step on both sides
- Grab handles: Qty 2
- 12" T aluminum tailgate w/slam latch
- Hose retainer
- 5 lb fire extinguisher
- Warning triangles: 3 pk

SUMMIT MODEL 7529 TELESCOPIC CRANE

- Capacity Rating: 7.5 K @ 6'
- Planetary winch @ 60' per minute
- Auto-release hook stow
- Boom support and hook anchor
- Proportional hyd system
- 26 gal hyd reservoir
- Full hyd rear outriggers
- ASE Phase 4 control system
 - NEW DIGITAL TOUCHSCREEN CAB PANEL



VMAC DTM70-H

- Direct-transmission mounted PTO multi-power system
- Rotary screw air compressor: 65 CFM @ 100 psi
- Hyd pump: 8 GPM pump @ 3000 psi in variable mode
- PTO: CHELSEA® 210 Series
- VMAC control panel
- Hannay Reels spring rewind reel w/1/2" x 50' air hose & FRL
- 15 gal air storage tank

LINCOLN ELECTRIC RANGER® 260MPX™ ENGINE DRIVEN WELDER (KOHLER®)

- 260A Multi-Process: MIG, TIG,stick
- 9500W continuous, 120/240V clean AC power
- CC-Stick: 35-260A
- Touch Start TIG: 20-250A
- CV-Wire: 14-28V
- 50' of 1/0 hot & ground welding leads
 - 300A ground clamp & electrode holder

PAINT & FINISH

- Paint
 - Oxford White YZ: Body exterior & interior
 - Black: crane & drawer pack
- Protective Coating
 - Cargo area, rear bumper work surface & steps
 - Fronts, side, tops, the rear, & lower edge of side packs
 - Wheel well reinforcement
- Custom Graphics Package
 - Full body wrap designed & installed by Yellow Frog Graphics

CHASSIS SPECIFICATION

- 2022 Ford F-600 4X4 RC
- GVWR: 22,000
- Engine: 6.7L Power Stroke® V8 Turbo Diesel
- HP: 330
- Exhaust brake
- Transmission: 10R140 TorqShift®
 - 10-Spd SelectShift® Automatic
- CA: 84"
- WB: 169.3"
- Wheels: 19.5" x 6.75"
- Tires: 245/70Rx19.5G BSW