



Summit 7 Series

Electrified Service Truck

STE11339

BODY CONSTRUCTION

- 12 ga galvanized body 11' LG.
- 22" D compartments
- 50" W cargo floor
- 50" T DS compartments
- 62" T P1 compartment
- 50" T P2-P4 compartments
- Tie-down rings in cargo area: Qty 6
- E-track in the cargo area
- Aluminum bonded doors w/full length piano-style hinges
- Automotive-style weather-stripping
- Ergonomic over molded three-point compression door latches
- Aluminum drip rail over compartment doors
- Gang locks on DS & PS

SUMMIT DRAWER SYSTEMS

- Aluminum combo drawer pack: NEW DESIGN
 - TDRSA-52T-30L-03-02-01-22R-00-01-03
 - 52" W x 18" D overall
 - One 5" D full-width top drawer
 - Left side
 - Three 3" drawers
 - Two 5" drawers
 - One 7" drawer
 - Right Side
 - One 5" drawer
 - Three 7" drawers
 - The top shelf spans the full width of the compartment
- Aluminum drawer pack: DRSA-36W-2-1-0-18D-3.625-WT
 - Three drawers, 36" W X 18"
 - Slide-out work tray



TORCH STORAGE COMPARTMENT

- The front section has reinforced floor, upper & lower vents
 - Torch bottle retainer w/ratchet strap
- The rear section has unistrut & adjust. aluminum shelves: Qty 3

ELECTRICAL & LIGHTING

- LED S/T/T light package
 - Flush mounted in bumper & light bar
- LED compartment lights
- LED Work Lights: Qty 6
- Seven-way RV-style trailer plug
- Backup alarm
- Electrical circuits controlled by control panels and master relay
 - Control panels in cab & P4
- Whelen Justice mini lightbar
- Wig Wag light system
- Vanair ELiMENT™ LiFePO4 Batteries
 - 100Ah capacity & 48V
- EPEQ™ INVERTER6000
 - 120/240VAC
- 120V & 240V outlets
- 12/24V jump start
- Seven-way RV-style trailer plug
- Backup camera
- LED Strip lights inside the rear bumper storage compartment

SUMMIT MODEL 4416 JOURNEYMAN ELECTRIC CRANE

- Capacity Rating: 4000 lbs.
- First stage hydraulic ext & second stage manual ext.
- Powered by EPEQ™ ELiMENT™ batteries
- Full manual outriggers
- Single-function wireless control



ADDITIONAL FEATURES

- Custom headache rack
- 30" top opening storage bumper
 - 2 ½" receiver tube
 - Built-in grip strut steps
 - Bumper stores EPEQ™ ELiMENT™ batteries & electrical components
- Grab handles: Qty 2
- 12" T aluminum tailgate w/slam latch
- Wilton 1765 vise
- E-track on cargo area walls
- Chassis-supplied wheel simulators
- CARR kick step
- 5 lbs. fire extinguisher
- Warning triangles: 3 pk

Vanair EPEQ™ AIR20

- Two Speed settings: 10 CFM & 20 CFM
- Vanair EPEQ™ smart controller
- Hannay Reels spring rewind reel w/1/2" x 50' hose & FRL
- 8 gal air storage tank

Lincoln Electric POWER MIG® 215 MPi™ Multi-Process Welder

- 220A Multi-Process: MIG, TIG, Stick
- Dual input voltage: 120V/230V
- Magnum® PRO 175L Gun

Lube Skid

- General Construction
 - Fabricated common shell aluminum tank
 - .190" 3003 aluminum construction
 - .130" Aluminum reel box
 - 12V operated pump lube systems
 - Powered by Vanair EPEQ battery system



LUBE SKID CONT.

- Lube Systems
 - Three 40 gal new oil systems
 - 12V new oil pump
 - Hannay Reels spring rewind hose reels with 1/2" x 50' hose
 - Graco EM8 metered nozzle
 - Graco EGP 12v On-Demand pump
 - One 80 gal used oil transfer system
 - 12V Used oil pump
 - Hannay Reels spring rewind hose reel w/ 3/4" x 25' hose
 - Ball valve, 4" pipe nipple and cap.
 - Graco EGP 12v Transfer pump
 - Samson reversing valve
 - Overflow protection

PAINT & FINISH

- Paint: Summit White GAZ
 - Body, lube skid & drawer pack
- Protective Coating
 - Cargo area
 - Bumper work surface, steps, & outriggers
 - Fronts, side, tops, the rear, & lower edge of side packs
 - Wheel well reinforcement
- Custom Graphics Package
 - Designed & installed by Yellow Frog Graphics

CHASSIS SPECIFICATIONS

- 2022 Chevrolet Silverado 6500HD 4x4
- GVWR: 22,500 lbs.
- Engine: Duramax® 6.6L Turbo-Diesel V8
- HP: 350
- Transmission: Allison 2700 Rugged Duty Series™
 - 6 spd automatic
- Exhaust brake
- WB: 165"
- CA: 84"
- Wheels: 19.5" x 6.75" steel
- Tires: 225/70R19.5G