



**Tandem Axle Fuel & Lube
Lyons & Hohl
STE11957**

Body Construction

- 12 ga galvanealed steel body 14.5' L
 - Includes rear reel compartments
- DS & PS under tank compartments, approx 10' L
- 4" rear bumper
- Aluminum bonded doors with full-length piano-style hinges
- Automotive-style weatherstripping
- Ergonomic overmolded three-point compression door latches
- Aluminum drip rail over compartment doors

Rear Reel Compartment

- Fold-up rear compartment door with heavy-duty gas struts and locking latch
- New product reels with nozzle holder brackets mounted across the top
- Used oil reel and diesel reel mounted at the bottom of the compartment
 - Fuel nozzle storage is designed to drain into the used filter box
- Phase 5 system operation panel
- Used filter box
 - Quick-disconnect drain
 - Ball valve tied into the used oil pump
 - The check valve prevents tank discharge back into the filter box
- Summit aluminum drawer pack

Electrical & Lighting

- LED S/T/T light package
 - Flush mounted
 - Integrated backup alarm
- Interior LED Strip Compartment Lights
 - including two on the rear reel compartment door
- Rigid LED work lights: Qty 23
 - Four rear-mounted lights activated when backing up
- Backup camera installed at the top of the rear reel compartment
- 3000W pure sine wave inverter

- 115V power outlets: Qty 2
- Amber WigWag lights
- Keyless entry

Master Control System

- Dual touchscreen control system
- Master touchscreen control panel located in the rear reel compartment
- Secondary touchscreen display located in the cab
- Controls system wired and programmed to match the truck configuration
- Controlled Systems
 - PTO activation
 - Exterior Work Lighting
 - Fuel tank work lights
 - Reel compartment work lights
 - Rear-facing work lights
 - Cargo area work light
 - Interior Lighting
 - Compartment interior lighting
 - Heat Systems
 - Red Dot heater

Summit Drawer Systems

Aluminum Drawer Pack

- Drawer Pack PN: XRSA-26W-2-1-0-18D-WT-3.125
- 26" W x 18" D
 - Two - 3" drawers
 - One - 5" drawers
- Pull out the sorting tray

Aluminum Drawer Pack

- Draer pack PN: DRSA-42-1-0-0-WT
- 42" W x 18" D
 - One 3" drawer
- Pull-out sorting tray

Aluminum Bolt Bin

- Bolt Bin PN: PBA-18-6W x 3T

- 18 Bins
- 6 bins W x 3 bins T
- Pull-out work tray
- Bolt bin cabinet doors

Additional Features

- Cargo area access ladder
- Grab handles: Qty 2
- Used oil filter drawer
- Adjustable aluminum shelves
- 10 lb. ABC fire extinguisher: Qty 2
 - Mounting brackets included
- Red dot heaters: Qty 2
 - DEF tank compartment
 - Rear reel compartment
- Hazmat placards

Fuel & Lube Systems

Chassis Hydraulic System

- Chelsea heavy-duty air-operated PTO
- Parking brake interface
- Single load sense hydraulic pump
- Sun Source load sense valve
- Summit hydraulic reservoir
 - 40-gal reservoir tank
 - 12V Cooler
 - Temp transducer
 - Thermal bypass valve
 - Big filter (Rated for 40 gpm)
- System filled with ISO 46 hydraulic oil

Hydraulically Driven Diesel Fuel Delivery System

- TransTech 2500 gal aluminum diesel storage tank
- Rochester fluid level gauge remote display
- Hydraulically driven diesel fuel pump with two speed delivery rate
 - Low speed set to 20 GPM

- High speed set to 40 GPM
- Blackmer Pump
- Thermal protection valve
- EMCO emergency shut-off system
- Hannay Reels electric rewind hose reel
 - 1 ¼" x 75' fuel-rated hose
- Fueler 100 nozzle
- LCR-II digital fluid meter
- Dual filter setup
 - 30 micron & 10 micron filter

Hydraulically Driven New Oil Delivery Systems: Qty 4

- Four 90-gal poly tanks
- Non-vented fill cap
- Desiccant breathers
- Isspro tank level gauge with remote readout
- Hydraulic pumps
- Graco EM8 nozzles
- Hannay Reels spring rewind reel
 - 1/2" X 50' hose assembly

Air Driven Used Oil Evacuation System

- One 200-gal poly tank
- 1" air diaphragm pump
- 1" directional Valve
- On-load/off-load through a single hose
- Isspro tank level gauge with remote readout
- Hannay Reels electric rewind hose reel
 - 1" x 50' suction hose assembly
 - 30" suction wand
- Overfill prevention switch

Air Driven Antifreeze Delivery Systems

- One 90-gal poly tank
- Graco 3/4" diaphragm pump
- Thermal pressure relief valve
- Isspro tank gauge with remote readout
- Hannay Reels spring rewind hose reel

- 1/2" x 50' pressure hose assembly

Air Driven DEF Delivery System

- One 200-gal poly tank
- Graco 1/2" diaphragm pump
- Hannay Reels electric rewind reel
 - 5/8" rubber DEF hose
- DEF automatic fuel meter shutoff nozzle
- Blowback system
- Heated, Vortex-lined DEF compartment with washout drains.

RC-40L Hydraulic Driven Air Compressor

- 40 CFM free air @150 psig
- 9-14 gpm @ 2100 psi
- Hannay Reels spring rewind hose reel
 - 1/2" x 50' hose assembly
- 19 gal air storage tank

Paint & Finishes

- **PPG Paint Process**
 - Paint: Deep Forest Green- Dupont 7498
 - Body, doors, tank
 - Paint: White
 - Compartment interiors
- **Vortex Protective Coating**
 - Cargo area walkway
 - Bumper surface and reel compartment door frame
 - Front of body boxes and
 - Wheel well reinforcement
 - Top of compartments
 - Interior of the reel compartment and DEF compartment
- **Rubberized Protective Coating**
 - Underside of the body
- **Vinyl Graphics**
 - Designed & installed by Yellow Frog Graphics

Chassis Specifications

- 2026 Peterbilt 567
- GVWR: 64,180 66,000
- Engine: Cummins X15
 - HP:
- Transmission: Allison® 4500 Rugged Duty Series™
 - 6-spd automatic
- CA: 190" CA