



Custom 10 Series
Stevens Engineers & Constructors
STE12055

Body Construction

- 10 ga galvanized body, 14' LG
- 22" D side packs
- 54" W cargo floor
- Tie-down rings on cargo area walls: Qty 6
- 62" T DS & PS compartments
- Bore bar storage cabinet at the front of the body
- Aluminum bonded doors with full-length piano-style hinges
- Automotive-style weatherstripping
- Ergonomic overmolded three-point compression door latches
- Aluminum drip rail over compartment doors
- Keyless entry on all compartment doors
- Gang locks on DS & PS

Summit Drawer Systems

Aluminum Combo Drawer Pack

- Drawer Pack PN: TDRSA-50T-30L-03-02-01-22R-01-01-03
 - 50" W x 18" D overall
 - Top: 50" W x 18" D
 - One 5" D full-width top drawer
 - Left side: 30" W x 18" D
 - Three 3" drawers
 - Two 5" drawers
 - One 7" drawer
 - Right side: 20" D x 18" D
 - One 3" drawer

- One 5" drawer
 - Three 7" drawers
- Top shelf spans the full width of the compartment

Aluminum Drawer Pack

- Drawer Pack PN: DRSA-30W-05-02-02-18D
- 30" wide X 18" deep
 - Five 3" drawers
 - Two 5" drawers
 - Two 7" drawers
- Integrated top shelf

Aluminum Drawer Pack

- Drawer Pack PN: DRSA-46W-02-01-00-18D-WT aluminum drawer pack
- 46" wide X 18" deep
 - Two 3" drawers
 - One 5" drawer
 - Pull-out sorting tray
- Integrated top shelf

Aluminum Bolt Bin

- Bolt Bin PN: PBA-21- 3W x 7H-WT: Qty 2
 - 21 bins
 - 7 H x 3 W
 - Pull-out sorting tray
 - Bolt Bin cabinet doors

Electrical & Lighting Features

- LED S/T/T light package
 - Flush-mounted in bumper & light bar
- LED compartment lights
- LED Rigid work lights: Qty 8
- LED standard work lights: Qty 2
- Whelen Justice series mini lightbar
- LED Door strip lights
- Wigwag lights

- Xantrex 2000W pure sine power inverter
 - GFCI outlet
- Speakers
- Backup camera
- Backup alarm
- Backup sensor kit

Additional Features

- Standard headache rack
- Custom bumper: 36" deep with 3/8" removable top plate
- Driver's side access steps on with grab handles
 - Grip strut installed in bumper steps
 - Illuminated side step
 - 2.5" receiver
- Pressurized compartments
- Carr 31" work truck steps: Qty 2
- DS full-length riser on top of the sidepack
- DS storage boxes on top of the side pack
 - 26" H x 22" D x 68" L" with top-opening doors
 - 26" H x 22" D x 56" L with barn style doors
- E-Track on each cargo wall
- Chock blocks with wheel wells with storage
 - DS & PS
- 12" H tailgate
- Wilton 1780XC Vise
- Hose retainer
- Bolt-in bulkhead
- Fuse kit
- Ram universal laptop stand located in the cab
- Summit wall organization panels to accommodate the Milwaukee PACKOUT™ modular storage system.
- Slide-out hose crimper shelf
- Door-mounted aerosol can holders
- Torch bottle retainer with ratchet straps

- Welding rod holders: Qty 2
- Hannay Reels torch reel with $\frac{3}{8}$ " x 50' hoses
- Hannay Reels dual arc manual rewind reel: 50' L

Summit 10629 Hydraulic Crane

- Capacity rating 10,000 lbs @ 6 feet
- Planetary winch @ 60' per minute
- Auto-release stow hook
- Boom support & hook anchor
- Proportional hydraulic system
- 32 gal hydraulic reservoir
- ASE Phase 4 control system
 - Control and monitor crane, outriggers, PTO, engine, air compressor & lights.
- Full hydraulic rear outriggers

Man-Bucket

- Man-bucket mode control system programming
- Remote tether
- Self-rescue kit
- Cargo area bucket retainer bracket with ratchet strap
- Winch cable retainer
- 5 lb. fire extinguisher bracket
- Estop Switch
- Aluminum trays: Qty 2

Miller EnPak® A60GBHW All-in-one Solution

- Kubota 24.8 hp diesel engine
- Control Panels: User interface, weld output, aux power, battery charge/crank assist
- Rotary screw air compressor
 - 60 CFM @ 175 psi, 100% duty cycle
 - 15-gal air storage tank
- Generator: 7000W continuous power

- 120V outlets: Qty 2
- 240V outlet
- Battery charger/crank assist: 12/24V
 - 150A charge
 - 300A battery boost
 - Battery booster cable set
- Hydraulic pump: Casappa variable-displacement pump
 - 8-16 gpm 3500 psi max, open center
- Welder
 - 325A Multiprocess weld capabilities
 - 100% duty cycle
 - DC stick: 30–325A DC
 - TIG: 20–325A
 - MIG/flux-cored: 15–40V
 - 50' of 1/0 hot & ground leads
 - quick disconnects
 - 300A ground clamps & electrode holder
- 20-gal hydraulic reservoir

Lube Systems

Air-driven New Oil Delivery Systems: Qty 2

- Two 50 Gal steel new oil tanks
- Tank level gauge for steel tanks
- Graco 5:1 product delivery pumps: Qty 2
- Hannay Reels spring rewind reel w/1/2" x 35' hose: Qty 2
- Graco EM8 metered nozzle: Qty 2

Hydraulic-driven 400# New Oil System

- Graco 55 gal drum
- Graco 1:1 hydraulic oil pump
- Graco Fireball 300 5:1
- 400# new oil pump kit
- Hannay Reels spring rewind hose reels
 - 1/2" x 50' hose assembly
- Graco metered nozzle

Air-driven Used Oil Evacuation System

- One 60-gal steel tank
- Samson 1" Air Diaphragm pump
- 1" Directional Valve
- Tank level gauge for steel tanks
- Hannay Reels air rewind hose reel
 - 1" x 50' suction hose
- 30" suction wand with quick couple
- Overfill prevention switch

Paint & Finishes

- **PPG Paint Process**
 - PPG Paint: Omaha Orange
 - Body exterior, crane, drawer packs, bolt bins, doors and accessories
 - PPG Paint: White
 - Compartment interiors
- **Vortex Protective Coating**
 - Cargo area, rear bumper & outriggers
 - Fronts, tops, the rear, & lower edge of side packs
 - Wheel well reinforcement
- **Rubberized Protective Coating**
 - Underside of the body
- **Graphics Package**
 - Designed and installed by Yellow Frog Graphics

Chassis Specifications

- 2026 Peterbilt 537 4x2 RC
- GVWR: 33,000 lbs
- Engine: Paccar PX-9
 - HP: 350
- Transmission: Allison® 3000 Rugged Duty Series™
 - 6-spd automatic
- CT: 128"